

The Turbotech clock cartridge will enable your Amiga to continually store the time and date in its own battery backed memory. The clock cartridge plugs into the back of the Amiga without the need to open up the computer. Fitting the clock cartridge does not invalidate your warranty.

INSTRUCTIONS

Connecting the Clock Cartridge

With the power to the Amiga turned off, plug the clock cartridge into the socket labelled 'DISK DRIVE' at the rear of the computer. If you already have a disk drive plugged into the socket, then plug the clock cartridge into the duplicate socket at the rear of the disk drive (all known drives have this socket).

Installing the software

- 1)** Switch the power to the computer on and boot up from your workbench disk in the normal way.
- 2)** Insert the Clock Cartridge Software Disk and double click on its icon to reveal the files on the disk. In order for the Amiga to know that the clock cartridge is present, a short program needs to be copied onto your 'Workbench' or 'Start-of-day' disk.
- 3)** Simply double click on the icon labelled 'INSTALL' and follow the on screen prompts. You will be asked for the name of the device in which you want the software installed. If you have a hard drive connected to your Amiga, simply enter the name of the 'boot partition' (usually DHO:, Workbench etc.). If you are installing onto a floppy disk, put your 'Workbench' or 'Start-of-day' disk in the internal disk drive and enter 'DFO:'.
- 4)** The file 'SETAMIGA' will be copied into the 'S' directory of the disk and the 'startup-sequence' will be modified accordingly.

Setting the time

- 5)** Once the installation is complete, you will need to set the Amiga's internal clock to the correct time. If you are unsure how to do this, please refer to your Amiga's manual.
- 6)** Lastly, you will need to copy the correct time from the Amiga's internal clock, into the clock cartridge. To do this, simply double click on the icon labelled 'SET CARTRIDGE' on the Clock Cartridge Software Disk.
- 7)** Everything is now complete! Every time you turn on your Amiga and boot from the installed disk, the correct time will be copied from the clock cartridge into the Amiga's internal clock.
- 8)** If at any point you need to alter the time, simply set the correct time in the Amiga's internal clock and use the 'SET CARTRIDGE' program to copy the time into the clock cartridge.

PLEASE NOTE:- The 25 way connector attached to one end of the clock cartridge is for cosmetic purposes only.